


Submittal Data Sheet

NOTES:

1. SEE O&M FOR REQUIRED INSTALLATION CLEARANCES.
2. DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.
3. DIMENSIONS ENCLOSED IN [] ARE IN MM.



Submittal Data Sheet

RATINGS AND CAPACITIES

Input (MBH):	750,000	BTU/HR
Output (MBH):	615,000	BTU/HR
Boiler Horsepower:	18.4	BTU/HR
Thermal Efficiency:	82.0%	BHP
Heating Surface:	131	Sq.Ft.
Water Content:	15.9	Gallons
Fuel:	Natural Gas or LP Gas	
Firing Rate:	Reliable Modulation	
Burner Turndown:	3:1	
Low NOx Emissions:	<10 ppm	
Inlet Gas Pressure (NG):	See Chart at right	
Inlet Gas Pressure (LP):	See Chart at right	

* This data supersedes data found on Table 3 of I&O Manual, per PRODUCT UPDATE issued June 6, 2024.

Shipping Weight, Approximate:	1,772	lbs
-------------------------------	--------------	-----

ASME Section IV (Max 160 PSIG / 210°F)

Setpoint range is 145-190°F



Adjustable, manual reset high limit setting of ≤ 200°F.

ASME HLW stamp MAWT is 210°F for the vessel. (For max setpoint, see Setpoint range.)

UL Certified to ANSI Z21.10.3/CSA 4.3



DIMENSIONS / CONNECTIONS

Height:	60 15/16"	(Note 1)
Width:	28 3/8"	(Note 2)
Length:	30 3/8"	(Note 3)
Supply Connection:	3"	
Return Connection:	3"	
Vent / Air Intake Connections:	4" Vent	6" Intake
Condensate / Appliance Drain Connection:	5/8" Condensate Tube	1" NPT Drain
Gas Connection:	1"	

NOTES:

1. Height dimension is from floor to top of jacket.

2. Length is from jacket front to jacket rear.

3. Dimensions shown are for reference only

FLOWS AND PRESSURE DROPS

Delta T	Flow (GPM)	ΔP (Ft. Hd)
20°FΔT	62 (Max)	1.81
40°FΔT	31 (Min)	0.46

Electrical Supply Options

<input type="checkbox"/>	120v/60hz/1ph (Standard)	7.5 amps
<input type="checkbox"/>	208v/60hz/1ph	6.6 amps
<input type="checkbox"/>	230v/60hz/1ph	6.4 amps
<input type="checkbox"/>	208v/60hz/3ph	6.0 amps
<input type="checkbox"/>	230v/60hz/3ph	6.0 amps
<input type="checkbox"/>	460v/60hz/3ph	3.0 amps

Blower Motor (hp)

1-1/2

Relief Valve Options

<input type="checkbox"/>	125 psi (STANDARD)
<input type="checkbox"/>	150 psi (OPTIONAL)

Inlet Gas Pressure

SIZE	Nat. Gas Min. ("w.c.)	LP Min. ("w.c.)	Max
500	5.0" w.c.	8.0" w.c.	14.0" w.c.
750	7.0" w.c.*		
1000	7.0" w.c.*		
1500	7.0" w.c.*		
2000	9.0" w.c.*		
2000s	7.0" w.c.		
2500	6.0" w.c.		
3000	6.0" w.c.		

* NOTE: Optional natural gas train with 4" w.c. minimum inlet gas pressure
ONLY AVAILABLE on sizes 750, 1000, 1500 & 2000.



Submittal Data Sheet

STANDARD EQUIPMENT		OPTIONAL EQUIPMENT												
PRESSURE VESSEL DESIGN		BOILER EQUIPMENT												
Copper Fin-tube construction Bronze header design Gasketless heat exchanger ASME Section IV certified "H" stamp MAWP 160 PSI & max design temp 250°F 5-year heat exchanger warranty 20-year thermal shock warranty	High limit w/ manual reset safety temperature control Water flow switch Low water cut-off with manual reset safety controller Outlet temperature sensor Combustion air switch Pressure and temperature gauge Safety relief valve (Optional pressures 30 - 150 PSI; See details above.)	<input type="checkbox"/> Low gas pressure venturi, 4" wc (AVAILABLE ONLY on Models 750-2000) [FACTORY INSTALLED OPTION ONLY] <input type="checkbox"/> Honeywell 7800 Series display with ModBus Module <input type="checkbox"/> Line Reactor Adds voltage / spike protection for the blower's VFD. (For areas with dirty voltage) <input type="checkbox"/> Outdoor Air Sensor <input type="checkbox"/> Condensate neutralizer: <input type="checkbox"/> 850 MBH <input type="checkbox"/> 1,200 MBH <input type="checkbox"/> 2,000 MBH <input type="checkbox"/> 5,000 MBH <input type="checkbox"/> Pump Kit (Boiler Circulation Pump, Pump Flange Kit Sized based on a 20°F Delta T) <input type="checkbox"/> Annual Maintenance Kit <input type="checkbox"/> System Temperature Sensor <input type="checkbox"/> Universal com. gateway (BacNet MS/TP, BacNet/IP, LonWorks) <input type="checkbox"/> Local / Remote Switch for Enable / Disable <input type="checkbox"/> Alarm bell with silencing switch <input type="checkbox"/> Relays: <input type="checkbox"/> General Alarm <input type="checkbox"/> Boiler Status <input type="checkbox"/> Conductor Sequencing Panel: (Contact Regional Manager with Questions.)												
COMBUSTION DESIGN		BURNER EQUIPMENT												
Maintenance-free ceramic burner Ultr-low NOx emissions (<10ppm) Whisper quiet operation (<50 dBA) Easy to service, 99% efficient industrial air filter Industrial cast aluminum blower assembly VFD Driven Blower Reliable electric spark-to-pilot ignition 10-year burner warranty Honeywell UV-Scanner	UL/FM/CSD-1 gas train Reliable Turndown Natural or LP gas Pilot gas valve / Pilot gas regulator Siemens SKP-75 gas valve Low and high gas pressure switches with manual reset	The Conductor Sequencing Panel manages multiple condensing & non-condensing, small & large heat output, new and/or existing boilers (full modulation), and steam or hot water applications. It helps improve system efficiency by selecting and modulating the right boiler to match operating conditions. The Conductor offers a single point boiler plant Energy Management System (EMS) interface including Modbus TCP/IP, Modbus RTU RS485, BACnet/IP and BACnet MSTP standard. If Lonworks needed, add for the separate Lonworks gateway.												
VENTING		TSBC Control Features												
Sealed or room air combustion Direct vent (sidewall or vertical) (Cat IV) Conventional venting (Cat II) NOTE: This is NOT a Cat 1 Vent appliance.	Advanced Boiler Modulation or Setpoint Intelligent Multipler Boiler Staging (8 Boilers) Building Management (BMS) Interface Outdoor Air Temperature Reset Warm Weather Shutdown Domester Hot Weather Priority Auxiliary Device Control - Boiler Pump - System Pump Adjustable setpoint or burner modulation with 1-9vDC input from BMS	Extended Warranty Options Available: <table border="1"> <tr> <th></th> <th><u>3-Year</u></th> <th><u>5-Year</u></th> <th><u>10 Year</u></th> </tr> <tr> <td><u>Parts Only</u></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> <tr> <td><u>Parts and Labor</u></td> <td>N/A</td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> </table>		<u>3-Year</u>	<u>5-Year</u>	<u>10 Year</u>	<u>Parts Only</u>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<u>Parts and Labor</u>	N/A	<input type="checkbox"/>	<input type="checkbox"/>
	<u>3-Year</u>	<u>5-Year</u>	<u>10 Year</u>											
<u>Parts Only</u>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>											
<u>Parts and Labor</u>	N/A	<input type="checkbox"/>	<input type="checkbox"/>											

Submittal Data Sheet

TSBC CONTROL FEATURES



Flexible, Field Selectable Control

- Remote Setpoint Control or Firing Rate Control
- Factory defaults simplify field programming
- Eleven settings to help control oversizing

Boiler Monitoring and Diagnostic Displays

- Boiler inlet and outlet sensors
- (OPTIONAL) System header sensor
- (OPTIONAL) Outdoor air sensor
- Modulation rate setpoint & modulating percent
- Boiler sequencing messages, alarms, hold & lockout messages
- Event history - Up to 10 alarm messages & data

Modulation Rate

- Modbus or 1-9vDC input boiler modulation control options
- Choice of six different control modes
- Adjustable PID for local or remote control

Advanced Availability

- If optional header sensor fails, TSBC automatically reverts back to the outlet sensor to allow continued operation.

Outdoor Air Reset

- Fine tune the water temp based on outdoor air temp for maximized comfort and fuel savings.

Requires optional outdoor air temp sensor.

- Frost protection enabled with optional outdoor air sensor

Pump Control

- Domestic Hot Water (DHW) Pump
- System Pump
- Pump Overrun for Heat Dissipation
- Boiler Pump

Peer-to-Peer Network

- Lead-lag sequencing for up to eight (8) boilers.
- Selectable Lead boiler rotation, 8-720 hours
- RJ11 plug in connections between units (Requires splitter)
- Rotation off feature for complex installations

Warm Weather Shutdown (WWSD)

- Boilers used primarily for building heat will automatically shut down when outdoor temp reaches programmable WWSD setpoint.
- Saves energy by preventing boiler, pump and / or system pump from starting
- Requires the optional outdoor air sensor

Other Features

- Domestic Hot Water Priority (DHWP)
- Rotation enable and disable
- Setpoint adjustable up to 230F for boilers and 200F for water heaters
- Defineable min. setpoint to reduce chance of condensing
- 3 pump control capable, Boiler, DHW, System